

| TECAPRO®



FIT FOR ANY PURPOSE

TECAPRO®
XB 9340 – 340 g/m²

MADE FOR METAL INDUSTRY EXPERTS

This fabric's unique blend composition provides unique shielding against intense sparks and heavy molten metal splashes.











HIGH STRENGTH






This fabric is uniquely strong and durable due to the high amount of para-aramid fibers, therefore avoiding premature hole formation.

COMFORTABLE

Feels soft and supple due to its high cotton content and our special permanent Comfort-Control finish.

TECHNICAL DATA	TECAPRO®	TEST METHOD
Quality	XB 9340	
Width	153 cm (+2/-1 cm)	ISO 22198: 2006
Weight	340 g/m ² (± 5%)	ISO 3801: 1977
Composition	co/para-aramid/Static-Control™ 74/25/1%	ISO 3572: 1976
Construction	4/1 satin	ISO 1833: 2020
Available finishes	Durable flame-retardant finish with Comfort-Control and Hydro-Tec	

Physical performance		
Tensile strength	1500 N x 1800 N (±10%)	ISO 13934-1: 2013
Care labelling		
Domestic laundering	    	
Industrial laundering	75 °C	
Protection	Multi-risk	
PPE requirements*	    	

CERTIFICATION*		
	Industrial flame & heat hazards	EN ISO 11612 A1, B1, C1, E2, F1; 2015 (A1 + A2 = 50 x ISO 15797 - 75 °C)**
	Electric Arc	EN IEC 61482-1-2, class 1: 2015, HRC/Category 2 (8 ≤ ATPV ≤ 25 cal/cm ²)
	Welding	EN ISO 11611, class 1: 2015
	Anti-static for explosion risk	EN 1149-5: 2018, EN 1149-3: 2004
	Liquid chemicals**	EN 13034: 2005 + A1: 2009
	General requirements***	EN ISO 13688: 2013

* Copyright symbols: NEN, Delft (Netherlands)

** Hydro-Tec finish only

*** Tested on specific colours

COLOURS

Dark-slateblue 42049	Denimblue 40518
-------------------------	--------------------

The colours shown are standard options available with a minimum order of 100 meters. This service program is subject to change. Please scan the QR code or visit [our website](#) for the latest overview of standard colours.



For any additional colours or specific colour combination requirements beyond this service, please contact your TenCate Protective Fabrics representative.

Ten Cate Protect B.V. is certified according:

Member of ETSA

Product certification:



All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TenCate Protective Fabrics Europe declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.