

| TECAPRO®



**FIT FOR ANY
PURPOSE**

TECAPRO®
XC 9001 – 265 g/m²

SUPREME ABRASION RESISTANCE











15% of polyamide to withstand high rates of friction and abrasion in tough working environments.






LIGHT WEIGHT, HIGH COTTON CONTENT

The perfect solution for hot conditions and high intensity work.

FITTED FOR HIGH THERMAL RISK ENVIRONMENTS

Provides protection in all environments, from welding, grinding, anti-static, heat and flame to chemical splashes and electric arc.

TECHNICAL DATA	TECAPRO®	TEST METHOD
Quality	XC 9001	
Width	153 cm (+2/-1 cm)	ISO 22198: 2006
Weight	265 g/m ² (± 5%)	ISO 3801: 1977
Composition	co/pa/Static-Control™ 84/15/1%	ISO 3572: 1976
Construction	3/1 twill	ISO 1833: 2020
Available finishes	Durable flame-retardant finish with Comfort-Control and Hydro-Tec	
Physical performance		
Tensile strength	1150 N x 500 N (±10%)	ISO 13934-1: 2013
Care labelling		
Domestic laundering	    	
Industrial laundering	75 °C	
Protection	Multi-risk	
PPE requirements*	    	

CERTIFICATION*		
	Industrial flame & heat hazards	EN ISO 11612 A1, A2, B1, C1, E2, F1; 2015 (A1 + A2 = 50 x ISO 15797 - 75 °C)**
	Electric Arc	EN 61482-1-2, class 1: 2009 HRC/Category 1 (4 ≤ ATPV ≤ 8 cal/cm ²)
	Welding	EN ISO 11611, class 1: 2015
	Anti-static for explosion risk	EN 1149-5: 2018, EN 1149-3: 2004
	Liquid chemicals***	EN 13034 + A1: 2009
	General requirements****	EN ISO 13688: 2013

* Copyright symbols: NEN, Delft (Netherlands).

** After pre-treatment (according to ISO 15797, 1 wash procedure 8 (75 °C) and 1 tumble drying (procedure A) (max. 70 °C outlet temperature).

*** Hydro-Tec finish only.

**** Tested on specific colours.

COLOURS

Cadet blue 41881	Dodger blue 41894	Gainsboro 41883
---------------------	----------------------	--------------------

The colours shown are standard options available with a minimum order of 100 meters. This service program is subject to change. Please scan the QR code or visit [our website](#) for the latest overview of standard colours.



For any additional colours or specific colour combination requirements beyond this service, please contact your TenCate Protective Fabrics representative.

Ten Cate Protect B.V. is certified according:



Member of ETSA



Product certification:



All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TenCate Protective Fabrics Europe declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.