DEFENDER®M



DEFENDER® M DM 9210 – 210 g/m²

SUPERIOR THERMAL PROTECTION

Protects against heat and flame (complies with EN ISO 11612 A1,A2,B1,C1: 2008) and offers an optimized protection against severe body burns caused by improvised explosive devices (IED's), blasts and fuel.

HIGHLY COMFORTABLE

Lightweight, breathable and excellent moisture absorption.

EXTREMELY DURABLE

Excellent resistance to wear, tear and fading are combined to provide a long useful garment life.



DEFENDER®M

TECHNICAL DATA	DEFENDER® M	TEST METHOD
Quality	DM 9210	
Width	163 cm (+2/-1 cm)	ISO 22198: 2006
Weight	210 g/m² (± 5%)	ISO 3801: 1977
Composition	Lenzing FR®/para-aramid/ polyamid/anti-static	
Construction	Ripstop plain	
Available finishes	Hydro-Tec™	

Physical performance		
Tensile strength	900 N x 800 N (±10%)	ISO 13934-1: 1999
Tear strength	35 N x 35 N (±10%)	ISO 13937-2: 2000
Abrasion	50.000 @ 12 kPa	ISO 12947-2: 2002
Dimensional stability	± 3%	ISO 5077: 2007
Air permeability	> 120 L/m²	ISO 9237: 1995
Heat resistance 180°C	± 5% shrinkage. Does not melt or self ignite	ISO 17493: 2000

Care labelling		
Domestic laundering	60° × 0 P	
PPE requirements*	(4)	

 $^{^{*}}$ Copyright symbols: NEN, Delft (Netherlands)

CERTIFICATION		
@	Industrial flame & heat hazards	EN ISO 11612 A1,A2,B1,C1: 2008
	Liquid chemicals**	EN 13034, type 6: 2005
<u>E</u>)	Anti-static for explosion risk	EN 1149-5: 2008, EN 1149-3: 2004

^{**} Hydro-Tec finish only





Ten Cate Protect B.V. is certified according:





All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TenCate Protective Fabrics Europe declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.