

| TECAWORK®



**ANY WORK,
ANYWHERE**

TECAWORK®
KG 9308 – 245 g/m²

POWERFUL ANTI-STATIC PROPERTIES

For workers that need protection in a potentially explosive atmosphere.

STRONG AND DURABLE

Truly fitted for hard-working environments thanks to its strength and greater abrasion resistance features, which will allow a longer garment life cycle.

INDUSTRIAL LAUNDERABLE

Engineered to retain its looks even after high-temperature industrial laundering – minimizing the cost of ownership.

TECHNICAL DATA	TECAWORK®	TEST METHOD
Quality	KG 9308	
Width	153 cm (+2/-1 cm)	ISO 22198: 2006
Weight	245 g/m ² (±5%)	ISO 3801: 1977
Composition	64/35/1% polyester/cotton/Static-Control™	ISO 1833: 2020
Construction	2/1 twill	ISO 3572: 1976
Available finishes	Standard: Easy Care, Optional: Hydro-Tec	
Physical performance		
Tensile strength	1500 N x 900 N (±10%)	ISO 13934-1: 2013
Tear strength	50 N x 40 N (±10%)	NEN-EN-ISO 13937-1: 2000
Dimensional change	Max. ± 3 %	ISO 5077: 2007 After 5x cleaning cycles at 75 °C ISO 15797: 2018
Care labelling		
Domestic laundering		NEN-EN-ISO 6330, 6N 60 °C: 2013
Industrial laundering	75 °C - ISO 15797 White: Colour:	Visit our website for the laundrying recommendations www.tencatefabrics.com Qualification label - ISO 30023

CERTIFICATION		
	Anti-static for explosion risk	EN 1149-5 (Test EN 1149-3)
	OEKO-TEX® STANDARD 100, class II	Centexbel; 1803034

COLOURS

Royal box 60624	Navy 63805	Mole grey 61094
--------------------	---------------	--------------------

The colours shown are standard options available with a minimum order of 100 meters. This service program is subject to change. Please scan the QR code or visit our website for the latest overview of standard colours.



For any additional colours or specific colour combination requirements beyond this service, please contact your TenCate Protective Fabrics representative.

Ten Cate Protect B.V. is certified according:



Product certification:



Ethically sourced cotton available via these programs:



All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TenCate Protective Fabrics Europe declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.